

Appl. No.: 10/572,710
Reply to Advisory Action of: 08/01/2008

RECEIVED
CENTRAL FAX CENTER
SEP 26 2008

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently amended) A An ~~mobile cellular telephone~~ apparatus comprising:

a display;

a processor ~~for~~ configured to controlling control the operation of ~~the~~ a mobile cellular telephone including the display;

an incline sensor arranged configured to detect inclination of the mobile telephone in a first plane, wherein the mobile cellular telephone has an inclinometer mode, in which the processor ~~receives~~ is configured to receive an indication of the detected incline in the first plane from the incline sensor and ~~controls~~ control the display to display, to a user of the mobile cellular telephone, a bar and an item, at a position within the bar dependent upon the received indication, the position of the item within the bar representative of the sense and amount of inclination of the mobile cellular telephone in the first plane.

2. (Currently amended) A An ~~mobile cellular telephone~~ apparatus as claimed in claim 1, wherein the processor receives real-time indications of the detected incline in the first plane from the incline sensor and controls the display

Appl. No.: 10/572,710

Reply to Advisory Action of: 08/01/2008

to move an item, in real-time, through positions dependent upon the received indications.

3. (Currently amended) A An ~~mobile-cellular-telephone apparatus~~ as claimed in claim 1, wherein the display has a first axis and the processor controls the display to display an item at a position along the first axis dependent upon the received indication.

4. (Currently amended) A An ~~mobile-cellular-telephone apparatus~~ as claimed in claim 1, wherein the incline sensor is arranged configured to additionally detect inclination of the mobile telephone in a second plane, orthogonal to the first plane, wherein, in the inclinometer mode, the processor receives an indication of the detected incline in the second plane from the incline sensor and controls the display to display a further item at a position dependent upon the received indication.

5. (Currently amended) A An ~~mobile-cellular-telephone apparatus~~ as claimed in claim 4, wherein the processor receives real-time indications of the detected incline in the first and second planes from the incline sensor and controls the display to move the item and the further item, in real-time, through positions dependent upon the received indications.

6. (Currently amended) A An ~~mobile-cellular-telephone apparatus~~ as claimed in claim 4, wherein the display has a first axis and a second axis orthogonal with the first axis and the processor controls the display to display the item at a position along the first axis dependent upon the received

Appl. No.: 10/572,710

Reply to Advisory Action of: 08/01/2008

indication of the detected incline in the first plane and the further item at a position along the second axis dependent upon the received indication of the detected incline in the second plane.

7. (Currently amended) A An ~~mobile cellular telephone~~ apparatus as claimed in claim 1 wherein the incline sensor is additionally ~~arranged~~ configured to detect inclination of the mobile telephone in a second plane, orthogonal to the first plane, and the processor in the inclinometer mode receives a first indication of the detected incline in the first plane and a second indication of the detected incline in the second plane from the incline sensor and controls the display to display the item at a position dependent upon the received first and second indications.

8. (Currently amended) A An ~~mobile cellular telephone~~ apparatus as claimed in claim 7, wherein the display has a first axis and a second axis orthogonal with the first axis and the processor controls the display to display the item at a co-ordinate position (i,j), wherein the first co-ordinate is dependent upon the received indication of the detected incline in the first plane and second co-ordinate is dependent upon the received indication of the detected incline in the second plane.

9. (Currently amended) A An ~~mobile cellular telephone~~ apparatus as claimed in claim 7, wherein the processor receives real-time indications of the detected incline in the first and second planes from the incline sensor and controls

Appl. No.: 10/572,710
Reply to Advisory Action of: 08/01/2008

the display to move the item, in real-time, through positions dependent upon the received indications.

10. (Currently amended) A An mobile—cellular—telephone apparatus as claimed in claim 1, wherein the incline sensor comprises a first pair of electrodes aligned along the first plane and partially immersed in a liquid for providing a first signal indicative of an incline in the first plane; and a second pair of electrodes aligned along a second plane, orthogonal to the first plane, and partially immersed in a liquid for providing a second signal indicative of an incline in the second plane.

11. (Currently amended) A An mobile—cellular—telephone apparatus comprising:

a display;

a processor ~~for~~ configured to controlling control the operation of ~~the~~ a mobile cellular telephone including the display;

a first incline sensor means for configured to detecting detect an inclination of the mobile telephone when in a first orientation; and

a second incline sensor means for configured to detecting detect an inclination of the mobile telephone when in a second orientation, wherein the mobile cellular telephone has an inclinometer mode, in which the processor is configured to determines determine an approximate orientation of the mobile telephone from inputs from the first and second incline sensor sensors means and automatically controls control the display

Appl. No.: 10/572,710
Reply to Advisory Action of: 08/01/2008

to display, to a user of the mobile cellular telephone, a first bar, a first item, a second bar and a ~~an~~ second item, wherein a position of the first item within the first bar is representative of the incline in the first orientation, and wherein ~~at~~ a position of the second item within the second bar is representative of the incline ~~for the determined~~ in the second orientation.

12. (Cancelled)

13. (Previously presented) The use of a mobile telephone as claimed in claim 1 for measuring an incline.

14. (Previously presented) The use of a mobile telephone as claimed in claim 1 for correcting an incline.

15. (Currently amended) A method comprising, ~~when the mobile telephone is in an inclinometer mode:~~

detecting inclination of ~~the~~ a mobile telephone in a first plane; and

controlling a display to display, to a user of the mobile telephone, a bar and an item, at a position within the bar dependent upon the detected inclination, the position of the item within the bar representative of the sense and amount of inclination of the mobile telephone in the first plane.

16. (Previously presented) A method as claimed in claim 15, comprising receiving real-time indications of the detected incline in the first plane and controlling the display to move an item, in real-time, through positions dependent upon the detected inclinations.

Appl. No.: 10/572,710

Reply to Advisory Action of: 08/01/2008

17. (Previously presented) A method as claimed in claim 15, wherein the display has a first axis and the method includes controlling the display to display an item at a position along the first axis dependent upon the detected inclination.

18. (Previously presented) A method as claimed in claim 15, comprising detecting inclination of the mobile telephone in a second plane, orthogonal to the first plane, wherein, in the inclinometer mode, the method includes receiving an indication of the detected incline in the second plane and controlling the display to display a further item at a position dependent upon the received indication.

19. (Previously presented) A method as claimed in claim 18, comprising receiving real-time indications of the detected incline in the first and second planes and controlling the display to move the item and the further item, in real-time, through positions dependent upon the received indications.

20. (Previously presented) A method as claimed in claim 18, wherein the display has a first axis and a second axis orthogonal with the first axis and the method includes controlling the display to display the item at a position along the first axis dependent upon the received indication of the detected incline in the first plane and the further item at a position along the second axis dependent upon the received indication of the detected incline in the second plane.

21. (Previously presented) A method as claimed in claim 15, comprising detecting inclination of the mobile telephone in a second plane, orthogonal to the first plane, and when in the

Appl. No.: 10/572,710

Reply to Advisory Action of: 08/01/2008

inclinometer mode, the method includes receiving a first indication of the detected incline in the first plane and a second indication of the detected incline in the second plane and controlling the display to display the item at a position dependent upon the received first and second indications.

22. (Previously presented) A method as claimed in claim 21, wherein the display has a first axis and a second axis orthogonal with the first axis and the method includes controlling the display to display the item at a co-ordinate position (i,j) , wherein the first co-ordinate is dependent upon the received indication of the detected incline in the first plane and second co-ordinate is dependent upon the received indication of the detected incline in the second plane.

23. (Previously presented) A method as claimed in claim 21, comprising receiving real-time indications of the detected incline in the first and second planes and controlling the display to move the item, in real-time, through positions dependent upon the received indications.

24. (Currently amended) A An mobile—cellular—telephone apparatus as claimed in claim 1, wherein the mobile cellular telephone emulates a spirit level when it is in the inclinometer mode.

25. (Currently amended) A An mobile—cellular—telephone apparatus comprising:

a display;

Appl. No.: 10/572,710

Reply to Advisory Action of: 08/01/2008

a processor configured to ~~for~~ controlling control the operation of ~~the~~ a mobile cellular telephone including the display;

an incline sensor ~~arranged~~ configured to detect inclination of the mobile telephone in a first plane, wherein the mobile cellular telephone has an inclinometer mode, in which the processor is configured to ~~receives~~ receive an indication of the detected incline in the first plane from the incline sensor and ~~controls~~ control the display to display, to a user of the mobile telephone, a bar and an item, at a position within the bar, dependent upon the received indication, wherein the position of the item within the bar provides an indication to the user of the incline of the mobile cellular telephone in the first plane, and wherein the processor is configured to position the item at a central location within the bar when the inclination of the mobile cellular telephone in the first plane is substantially zero.

26. (New) A computer readable medium encoded with computer executable instructions for performing operations to detect and display an inclination comprising:

Detecting an inclination of a mobile telephone; and

controlling a display to display, to a user of the mobile telephone, a bar and an item, at a position within the bar dependent upon the detected inclination, wherein the position of the item within the bar is representative of the sense and amount of inclination of the mobile telephone.